



## Mini-Wright Standard Peak Flow Meter Technical specifications

**Tradition and Innovation** - Visionary thinking and a fascination with technology have guided us throughout our history to develop innovative products of outstanding reliability. Anticipating trends to improve the quality of life.

 **CLEMENT CLARKE  
INTERNATIONAL**

# Mini-Wright Standard PFM

## Technical specifications



### Mini-Wright Standard PFM

Dimensions nominal	157 x 44mm - w/o mouthpiece, 210 x 44mm - with mouthpiece	
Weight	76g - with mouthpiece	
Measurement Range	60 - 880 L/min (EU Scale)	60 - 880 L/min (ATS Scale)
Accuracy	±10% or 10 L/min (EU Scale)	±10% or 20 L/min (ATS Scale)
Repeatability	≤ 5 L/min (EU Scale)	±5% or 10 L/min (ATS Scale)

Product	Part Codes
Mini-Wright Standard PFM (EU Scale)	3103387
Mini-Wright Standard PFM (ATS Scale)	3103085

### Disposable Expiratory One-Way Valve Mouthpieces

Adult (box of 100 (5 x 20))	3122062
Adult (box of 200)	3122064
Adult (box of 500)	3122066
Paediatric Adaptors (pack of 20)	3122120

### Universal Mouthpieces - single patient use

Adult (pack of 1)	3103051
Adult (pack of 15)	3103095

## Product information

The Mini-Wright Standard PFM is the market's leading peak flow meter. It is lightweight and portable, ideal for adults and children. The Mini-Wright Standard PFM is referred to as the 'Gold Standard' for asthma management. It is predominantly used for taking peak flow measurement, helping patients to manage their asthma.

- Available with ATS and EU scale
- Individually calibrated for absolute accuracy
- Wide range of consumables available
- Easy-to-read scale

Mini-Wright Standard  
is manufactured  
in accordance with all  
appropriate EU regulations.

© CLEMENT CLARKE  
INTERNATIONAL Ltd

CLEMENT CLARKE INTERNATIONAL Ltd Edinburgh Way Harlow Essex CM20 2TT, GB  
Phone +44 (0)1279 414969 Fax +44 (0)1279 456300 resp@clement-clarke.com www.clement-clarke.com